IN THE CLAIMS:

1. (Currently Amended) A wireless device for connecting to one or more network node devices, the network node devices connected to one or more wirelines, the wireless device comprising:

one or more wireless signal generators supporting one or more wireless connections;

one or more memories comprising an identifier ~~corresponding to~~ identifying the wireless device;

one or more negotiators that negotiate with the network node device in order to establish a connection to one or more wirelines connected to the network node; and

a requesting process that requests, through ~~one or more messages~~ a message sent to the network node device, bridging to a call in progress, the ~~one or more messages~~ message comprising the request for bridging and the identifier.

2. (Currently Amended) A wireless device for connecting to one or more network node devices, the network node devices connected to a plurality of wirelines, the wireless device comprising:

one or more wireless signal generators supporting one or more wireless connections;

one or more memories comprising an identifier, wherein the identifier ~~corresponds to~~ identifies the wireless device;

a negotiator that negotiates with the network node device in order to establish a connection to one or more wirelines connected to the network node; and

a requestor that requests privacy through ~~one or more messages~~ a message sent to the network node device, the ~~one or more messages~~ message comprising the request for privacy and the identifier.

3. (Currently Amended) A method of joining a call in progress from a wireless device through wireless communication with a network node device comprising the steps of:

        initiating a connection by the wireless device between the wireless device and the network node device;

5   signaling the network node device by the wireless device to join a call in progress already connected through said network node device, the step of signaling comprising communicating a request to join the call in progress and an identifier to the network node device, wherein the identifier identifies the wireless device; and

        joining the call in progress.

10

4. (Original) The method of claim 3 further comprising the step of communicating with the network node device to establish the eligibility of the wireless device to join a call in progress.

15   5. (Canceled)

6. (Currently Amended) A method of establishing call privacy for a wireless device connected to a network node device comprising signaling by the wireless device to the network node device that privacy is requested, the step of signaling comprising

20   communicating a request for privacy and an identifier to the network node device, wherein the identifier identifies the wireless device.

7. (Original) The method of claim 6 further comprising the step of communicating with the network node device to establish the eligibility of the wireless device to request

25   privacy.

8. (Currently Amended) A storage medium containing a computer program to direct a wireless device to initiate connection with a network node device, the computer program having the steps of:

30   signaling, by using at least one pre-established command channel, a request for a connection;

3

communicating an identifier from the wireless device to the network node device, wherein the identifier ~~corresponds to~~ <u>identifies</u> the wireless device;

selecting a wireless signaling method to be used between the wireless device and the network node device; and

5   requesting, through ~~one or more messages~~ <u>a message</u> sent to the network node device, bridging to a call in progress, the ~~one or more messages~~ <u>message</u> comprising the request for bridging and the identifier.

9. (Currently Amended) A storage medium containing a computer program to direct a

10   wireless device to initiate connection with a network node device, the computer program having the steps of:

signaling, by using at least one pre-established command channel, a request for a connection;

communicating an identifier from the wireless device to the network node

15   device<u>, the identifier identifying the wireless device</u>;

selecting a wireless signaling method to be used between the wireless device and the network node device; and

requesting privacy through ~~one or more messages~~ <u>a message</u> sent to the network node device, the ~~one or more messages~~ <u>message</u> comprising the request for

20   privacy and the identifier.